

Directorate of Public Works, Fort Benning requires a 66HP Excavator to support grounds maintenance and horizontal surface maintenance in performance of the BASEOPS contract. 66HP Excavator should have the following characteristics and key features. Request Kubota, Model KX080-4S2, or Equal.

KEY FEATURES

- Cabin Features
 - Enclosed
 - ROPS / OPG: TOP Guard, Level I
- Track Type
 - Rubber
- Engine
 - Net Output: NLT 60 hp @ 2000 rpm
 - Double element air filter
 - Auto idling system
 - Water separator
- Dimensions
 - Overall Length: NGT 22'
 - Overall Height: NGT 9'
 - Overall Width: NGT 8'
- Minimum Ground Clearance
 - NLT 12.0"
- Hydraulic System
 - Pump Capacity: NLT 22 gpm
 - Auxiliary Hydraulic Flow: NLT 26 gpm
 - Maximum Breakout Force, Bucket: NLT 14000 lbf
 - Maximum Breakout Force, Arm: NLT 8000 lbf
 - Pressure accumulator
 - Hydraulic pressure checking ports
 - Third line hydraulic return
 - 2-pump load sensing system
 - Adjustable maximum oil flow on auxiliary hydraulic circuits 1 and 2
- Shoe Width
 - NLT 16"
- Hydraulic Angle Blade Dimensions
 - Width: NLT 7'
 - Height: NLT 20"
 - Angle: NLT 25 deg
- Operating Weight (including operators weight @165 lbs)
 - NGT 20000 lbs

- Operator's Space
 - Cab with A/C
 - Digital panel with diagnosis function
 - Retractable seat belt
 - Deluxe Suspension Seat
 - Cupholder
 - Moveable consoles
 - Air conditioner
 - Window Guttering
 - Hydraulic pilot control levers with wrist rests
 - Travel levers with foot pedals
 - Two pattern selection system
 - 12V power source
 - Cup holder
 - Horn
- Undercarriage
 - Dozer blade with float function
 - 1 × upper track roller
 - 5 lower track rollers on each side
 - 2-speed travel switch on dozer lever
 - 2-speed travel with auto-shift
- Bucket
 - Width: NLT 36"
 - Hydraulic Thumb
- Additional Features
 - Tool box
 - Grease gun holder