

Directorate of Public Works, Fort Benning requires a 15 FT Batwing Flex Mower to support grounds maintenance and horizontal surface maintenance in performance of the BASEOPS contract. 15 FT Batwing Flex Mower should have the following characteristics and key features. Request John Deere, Model FC15E, or Equal.

KEY FEATURES

- CUTTING WIDTH
 - NLT 15'
- CUTTING HEIGHT
 - Between 1" to 16"
- OVERALL LENGTH
 - NGT 18'
- TRANSPORT WIDTH
 - NGT 10'
- DECK HEIGHT
 - NLT 10"
- DRIVELINE PROTECTION
 - Protection: No-size, self-adjusting slip clutch
 - Profile: Multispline/star
- NUMBER OF GEARCASES
 - 4
- BLADEHOLDER
 - Round pan (stump jumper)
- BLADE (STANDARD)
 - Stump-jumper, single-suction blade
- ROTATION
 - Outward
- BLADE-TIP SPEED
 - NLT 520 rpm
- HITCH CATEGORY
 - Standard self-level clevis hitch
 - Narrow-profile width
- MINIMUM TRACTOR PTO FORCE POWER
 - NLT 50 hp
- WEIGHT (LESS ATTACHMENTS)
 - NGT 4600 lb
- WING HYDRAULICS
 - Wing lift: Simultaneous with spring-assist unfolding
 - Wing flex:
 - 90 degrees up for transport
 - Between -22° to 45° working angles

- WHEELS
 - Non-row width adjustable
 - No suspension
- TIRES
 - 4-bolt, 16 PR severe-duty agricultural
- ADDITIONAL BASE FEATURES
 - 2 SCV connections