

PUMPING EQUIPMENT SPECIFICATIONS – Minimum Requirements

SYSTEM:	(1) Pumping equipment designed to deliver Diesel/Gasoline Fuel up to 30 GPM through the first reel.
POWER TAKE OFF:	(1) High speed, double gear clutch shift PTO with controls and safety indicator light located in Cab.
EQUIPMENT CONTROLS:	(1) Factory installed 2-position rocker switch in cab with park brake interlock function requiring emergency brake to be set prior to activation.
PTO SHAFT:	(1) High torque drivelines with spline slip joint and grease fittings.
PUMP BRACKET:	(1) Heavy duty welded steel channel saddle type.
PUMP	(1) Blackmer TX1.5 for the pumping system.
PUMP STRAINER:	(1) Allegheny Welded for the pumping system.
METER/REGISTER:	(1) Tuthill Non Custody Transfer with no strainer with no air eliminator and no preset, no back pressure check valve and Tuthill mechanical register for the pumping system located in rear equipment cabinet.

HOSE REEL:	(1)	Hannay Electric rewind with vapor proof motor and rewind button, industrial grade battery cable, and 70-amp breaker with 9-amp fuse. Reels are in the rear cabinet.
HOSE:	(1)	1"X100ft delivery hose for the pumping system.
NOZZLE:	(1)	Automatic 1" OPW with swivel and quick disconnect for the hose.

SAFETY EQUIPMENT AND ACCESSORIES

PLACARDS:	(8)	DOT Rigid Plastic Placards - Slide-In Holders with 4 each 1203 and 1993 placards
FIRE EXTINGUISHER:	(1)	10lb. Fire Extinguisher
TRIANGLE KIT:	(1)	Warning triangle reflector kit included.
BUCKET:	(1)	5-Gallon DOT approved heavy-duty metal bucket.
SPILL PADS:	(1)	Case emergency absorbent pads.
BACKUP CAMERA:	(1)	Heavy-duty color CCD camera with 150° wide angle view and auto infrared for night vision. Stand alone 7" TFT LCD color monitor mounted in cab.

LIGHTS

WORK LIGHT:	(1)	Betts Full swivel LED Worklight w/ On-Off Switch located at the rear of the driver's side of the unit.
WORK LIGHT:	(1)	14-inch Spot Flood LED located on the overturn rail on the driver's side of the unit.

- | | | |
|--------------------|-----|---|
| WORK LIGHT: | (1) | Betts Full swivel LED Worklight w/ In-Cab Dash Switch located at the rear of the curb side of the unit. |
| WORK LIGHT: | (1) | 14-inch Spot Flood LED located on the overturn rail on the curb side of the unit. |