

Directorate of Public Works, Fort Benning requires a 47HP Excavator to support grounds maintenance and horizontal surface maintenance in performance of the BASEOPS contract. 47HP Excavator should have the following characteristics and key features. Request Kubota, Model KX057-5 Angle Blade, or Equal.

KEY FEATURES

- Cabin Features
 - Enclosed
 - ROPS / OPG: TOP Guard, Level I
- Track Type
 - Rubber
- Engine
 - Gross Output: 47.6 hp/ 2200 rpm
 - Net Output: 46.4 hp/ 2200 rpm
 - Displacement: 159.6 cu. in
- Dimensions
 - Overall Length: 18' 1"
 - Overall Height: 8' 4"
 - Overall Width: 6' 5"
- Minimum Ground Clearance
 - 12.2"
- Hydraulic System
 - Pump Capacity: 14.8 gpm Variable x2
 - Auxiliary Hydraulic Flow: 19.8 gpm- AUX1, 9.8 gpm- AUX2
 - Maximum Breakout Force, Bucket: 10172 lbf
 - Maximum Breakout Force, Arm: 5463 lbf
- Travel Speed
 - Minimum Speed: 1.7 mph
 - Maximum Speed: 3.0 mph
- Maximum Traction Force
 - 10139 lbf
- Tumbler Distance
 - 6' 6"
- Crawler Length
 - 8' 2"
- Shoe Width
 - 15.7"
- Unit Swing System
 - 9.2 rpm

- Angle Blade Dimensions
 - Width: 6' 5.2"
 - Height: 16.7"
 - Maximum Lift Above Ground: 20.1"
 - Maximum Drop Below Ground: 18.3"
 - Angle: Left/Right: 25 deg
- Hydraulic Oil Capacities
 - Reservoir: 11.1 gal
 - System: 20.3 gal
- Fuel Capacities
 - 19.3 gal
- Operating Weight (including operators weight @165 lbs)
 - 13051 lbs
- Operator's Space
 - Enclosed Cab with A/C
 - Digital panel with diagnosis function
 - Retractable seat belt
 - Deluxe Suspension Seat
 - Cupholder
 - Moveable consoles
 - Air conditioner
 - Window Guttering
 - Hydraulic pilot control levers with wrist rests
 - Travel levers with foot pedals
 - Two pattern selection system
 - 12V power source
 - Cup holder
 - Horn
- Bucket
 - Width: 24"
 - Hydraulic Thumb
- Additional Features
 - Tool box
 - Grease gun holder