

Directorate of Public Works, Fort Benning requires a 40HP Excavator to support grounds maintenance and horizontal surface maintenance in performance of the BASEOPS contract. 40HP Excavator should have the following characteristics and key features. Request Kubota, Model KX040-4 6-in-1 Blade, or Equal.

KEY FEATURES

- Cabin Features
 - Enclosed
 - ROPS / OPG: TOP Guard, Level I
- Track Type
 - Rubber
- Engine
 - Net Output: NLT 38 hp @ 2200 rpm
- Dimensions
 - Overall Length: NLT 16'
 - Overall Height: NGT 9'
 - Overall Width: NGT 6'
- Minimum Ground Clearance
 - NLT 12.0"
- Hydraulic System
 - Pump Capacity: NLT 24 gpm
 - Auxiliary Hydraulic Flow: NLT 17 gpm on AUX1, NLT 9 gpm on AUX2
 - Maximum Breakout Force, Bucket: NLT 9000 lbf
 - Maximum Breakout Force, Arm: NLT 4000 lbf
- Shoe Width
 - NLT 16"
- 6-in-1 Blade Dimensions
 - Width: NLT 5' 6"
 - Height: NLT 12"
 - Maximum Lift Above Ground: NLT 16"
 - Maximum Drop Below Ground: NLT 20"
 - Angle
 - Left/Right: NLT 25 deg
 - Tilt: NLT 10/10 deg
- Operating Weight (including operators weight @175 lbs)
 - NGT 11000 lbs
- Bucket
 - Width: NLT 24"
 - Hydraulic Thumb
- Additional Features
 - Tool box
 - Grease gun holder

- Operator's Space
 - Enclosed Cab with A/C
 - Digital panel with diagnosis function
 - Retractable seat belt
 - Deluxe Suspension Seat
 - Cupholder
 - Moveable consoles
 - Air conditioner
 - Window Guttering
 - Hydraulic pilot control levers with wrist rests
 - Travel levers with foot pedals
 - Two pattern selection system
 - 12V power source
 - Cup holder
 - Horn