

- **Sound Proof ACOUSTIC PANELS**
- **Must be wall mountable with angled impaling clips**
- **Panels must be even and flush when mounted side by side**
- **Color preferred is beige, cream color or similar neutral color**
- **Thickness of 1"**
- **Sound deadening and durable to block sound from one room to another**
- **Light weight preferred**
- **Able to be modified for fitment without compromising quality and effectiveness**
- **The ratings are expressed as a value between 0.00 and 1.00. 0 means no sound is absorbed, 1 means all sound is absorbed. Rating of 1.00 is REQUIRED**
- **All components shall have a Class A Flammability rating per ASTM E-**
- **84: Surface Burning Characteristics of Building Materials, with a Flame Spread of 25 or less and Smoke Developed of 450 or less**
- **Shall have static dissipative properties to prevent the build-up of static electricity and unwanted high-voltage sparks or electrical discharge.**

- Acoustic Panel: 1" (120x36x1) QTY: 1
- Acoustic Panel: 1" (120x48x1) QTY: 20
- Acoustic Panel: 1" (96x48x1) QTY: 36
- Acoustic Panel: 1" (120x24x1) QTY: 3
- Acoustic Panel: 1" (96x24x1) QTY: 3
- Acoustic Panel: 1" (96x36x1) QTY: 3