

LRS-16 Gen 3 NOT scout



Photo & Video Adapters

- Nikon Digital SLR Cameras
- Canon Digital SLR Cameras
- Sony, Canon, & other video Cameras



External IR Illuminator

Enhances the performance of the night vision system under extreme low-light conditions. 808 nM wavelength



Canon EOS to C-mount Adapter

Nikon AF /G to C-mount Adapter

Specifications

Diopter Adjustment:	+2 to -6
Battery:	CR123 Lithium (1)
Battery Life:	40 hours
Dimensions (in):	5.4 x 3.0 x 2.25
Dimensions (cm):	13.7 x 7.6 x 5.7
Weight:	12 oz (340 g)
Operating Temp:	-51 to +49 C
Storage Temp:	-51 to +85 C

Export of this product is strictly prohibited without a valid export license issued by the US Dept of State as prescribed in the International Traffic in Arms Regulation (ITAR), Title 22, Code of Federal Regulation, Parts 120-130



LRS-16

Camera and Video based
Night Vision Surveillance
System

The new LRS-16 is a state-of-the-art Generation 3 advanced night vision system that has been designed for all night time applications. The LRS-16 offers superior performance and image clarity while being easily adaptable to Nikon and Canon SLR cameras. NO back-focus is required because the Nikon and Canon camera adapters are factory pre-set. Simply snap-on and start recording. You can even use your Canon and Nikon lenses.

The LRS-16 is designed and built to ensure the highest quality and durability under the most difficult customer conditions. The camera adapters provide bright imaging and high resolution across the entire frame - and you will never see "circular" images. We provide full-format 35mm sensor coverage. Three models are available to fit your applications and budget and we offer a 72lp/mm Pinnacle tube. A variable gain unit is also available.

Features



- C-mount objective lens
- Built-in invisible IR illuminator
- Full-format 35mm sensor coverage
- Light-weight construction
- CR123 Lithium battery

15525 E El Lago Blvd, Fountain Hills, AZ 85268

www.securitymci.com

908 553-0005 ph

info@securitymci.com