



TRUE FOOD SERVICE EQUIPMENT, INC. • 2001 East Terra Lane • O'Fallon, Missouri 63366-4434  
ph. 636.240.2400 • toll free 800.325.6152 • fax 636.272.2408 • parts fax 636.272.9471 • www.truemfg.com

|              |          |         |       |
|--------------|----------|---------|-------|
| PROJECT NAME | LOCATION |         | AIA # |
| ITEM #       | QTY      | MODEL # | SIS # |

# SPEC SERIES®

ROLL-THRU SOLID SWING DOOR HEATED CABINET

|        |               |               |               |
|--------|---------------|---------------|---------------|
| models | STR2HRT-2S-2S | STA2HRT-2S-2S | STG2HRT-2S-2S |
|--------|---------------|---------------|---------------|



## STR2HRT-2S-2S

|          |   |
|----------|---|
| Exterior | Stainless steel door, front & sides.                            |
| Interior | Stainless steel side walls, back, floor, door liner, & ceiling. |


## STA2HRT-2S-2S

|          |   |
|----------|---|
| Exterior | Stainless steel door, front & sides.                            |
| Interior | Aluminum side walls & back.<br>Stainless steel floor & ceiling. |

## STG2HRT-2S-2S

|          |   |
|----------|---|
| Exterior | Stainless steel door, with matching aluminum sides.             |
| Interior | Aluminum side walls & back.<br>Stainless steel floor & ceiling. |


## plan view



ELEVATION



RIGHT VIEW



PLAN VIEW

## SPECIFICATIONS

| Dimensions  | in.              | mm.           |
|-------------|------------------|---------------|
| Length      | 68               | 1728          |
| Depth       | 37 1/2           | 953           |
| Height      | 83 3/4           | 2128          |
| Electrical  | U.S.             | International |
| Watts       | 4000             |               |
| Voltage     | 115/208-240/60/1 |               |
| NEMA        | N/A              |               |
| Cord Length | N/A              | N/A           |

† Depth does not include 4 1/8" (105 mm) for ramp each side.  
\* Height does not include 1" (26 mm) for system mechanical components.  
Note: Unit pre-wired at the factory ready to be hard-wired at the install location to a 115/208-240/60 Hz dedicated circuit.

Specifications subject to change without notice.  
Chart dimensions are rounded up to the nearest 1/8" (millimeters rounded up to the next whole number).



APPROVALS

AVAILABLE AT



TRUE FOOD SERVICE EQUIPMENT, INC. • 2001 East Terra Lane • O'Fallon, Missouri 63366-4434  
ph. 636.240.2400 • toll free 800.325.6152 • fax 636.272.2408 • parts fax 636.272.9471 • www.truemfg.com

|              |          |         |
|--------------|----------|---------|
| PROJECT NAME | LOCATION | AIA #   |
| ITEM #       | QTY      | MODEL # |
|              |          | SIS #   |

# SPEC SERIES®

ROLL-THRU SOLID SWING DOOR HEATED CABINET

|        |               |               |               |
|--------|---------------|---------------|---------------|
| models | STR2HRT-2S-2S | STA2HRT-2S-2S | STG2HRT-2S-2S |
|--------|---------------|---------------|---------------|



## standard features

### HEATER SYSTEM

- Cabinet designed to provide holding temperatures of 140°F to 180°F (60°C to 82.2°C). Heating system controlled by exterior on/off switch and electronic temperature control.
- Two (2) stainless steel (for corrosion resistance), finned tube heating elements per section (1000 watts each) for uniform generation of electric heat. Cabinet comes with a total of 4000 watts.
- Equipped with low-velocity fans to assure even temperature distribution throughout the cabinet. Fans are controlled by exterior on/off switch.
- Manually controlled vent located on top of the cabinet for positive humidity control.

### CABINET CONSTRUCTION

- Stainless steel breaker caps.
- Insulation - entire cabinet structure and solid door are foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

- One (1) heavy gauge stainless steel ramp per door.
- Designed to accept roll-in racks (inboard castors) with a maximum dimension of 27"L x 29"D x 66"H (686 mm x 737 mm x 1677 mm).

### DOORS

- Lifetime guaranteed bolt style door locks standard.
- Lifetime guaranteed heavy duty all metal working door handles.
- Positive seal self-closing doors with 120° stay open feature. Lifetime guaranteed external cam lift door hinges, Three (3) per door section.
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.

### LIGHTING

- Incandescent interior lighting; lights activated by exterior on/off switch, safety shielded.

### MODEL FEATURES

- Exterior, color coded, temperature display; accurate direct reading of internal cabinet temperature.

- Designed to hold warm baked or cooked food. Cabinet is not designed to heat ambient or cold product.
- Interior bumpers protect cabinet walls from abuse caused by roll-in carts.
- 12" x 20" (305 mm x 508 mm) pan for water included, if additional humidity is required.
- NSF/ANSI Standard 4 compliant for open food product.

### ELECTRICAL

- True requires that a sole use circuit be dedicated for the unit.
- Unit pre-wired at the factory ready to be hard-wired at the install location to a 115/208-240/60 Hz dedicated circuit.

### OPTIONAL FEATURES/ ACCESSORIES

(upcharge & lead times may apply)

- Field reversible hinge
- Security package.

#### WARRANTY\*

Three year warranty on all parts and labor.  
(U.S.A. only)

\*RESIDENTIAL APPLICATIONS: TRUE assumes no liability for parts or labor coverage for component failure, factory defect or any other damages for units installed in non-commercial foodservice or residential applications.

METRIC DIMENSIONS ROUNDED UP TO THE  
NEAREST WHOLE MILLIMETER

SPECIFICATIONS SUBJECT TO CHANGE  
WITHOUT NOTICE



| Model           | Elevation | Right | Plan | 3D | Back |
|-----------------|-----------|-------|------|----|------|
| ST( )2HRT-1S-1S |           |       |      |    |      |